

DATASHEET

QUICK ROLL R



GENERAL

Art.Nr:	H-576-200-RIGHT	Standards:	EN 12841:2006/B, EN 12841:2024/B, EN 567:2013
GTIN:	8053841302989	Net weight:	0.26 kg
Customs tariff number:	76169990	Gross weight:	0.34 kg

DATASHEET

QUICK ROLL R

Innovative right-hand ascender handle with integrated pulley, ideal for rope access and rescue. Used in conjunction with a self-braking descender it allows for ascending the work rope.

Main features:

- overmolded, ergonomic handle ascender, designed for greater efficiency when pulling and increased resistance to wear and tear;
 - cam opening lever usable with one hand; patented system for unlocking the cam, with just one downwards movement necessary;
 - steel cam, manufactured with technology that implements the resistance to wear and tear. Equipped with a set of teeth that protects the wear of the rope, but it is equally effective in blocking and ascending the rope. It also has three slots to prevent the accumulation of mud and reduce the effort needed to slide the device up the rope under any condition (muddy rope, frozen etc.);
 - two attachment holes for various possible uses, anti-inversion cam system, secondary hole for connecting a quick link for an etrier.
- Attention! The integrated pulley is not PPE and it can only be used as an additional aid to the ascent, as per the methods shown, but not for hauling people and/or material.

FEATURES

Colour:	Black, Orange
---------	---------------

Maximum lifetime:	12 years
-------------------	----------

Min. temperature:	-29 °C
-------------------	--------

Max. temperature:	40 °C
-------------------	-------

UIAA compliance:	Yes
------------------	-----

Working Load Limit:	140 kg
---------------------	--------

Patent status:	Patented
----------------	----------

Individually tested:	Yes
----------------------	-----

Ascender type:	hand_ascenders
----------------	----------------

DIMENSIONS

Min. rope diameter / EN 12841:	10 mm
--------------------------------	-------

Max. rope diameter / EN 12841:	13 mm
--------------------------------	-------

Min. rope diameter / EN 567:	8 mm
------------------------------	------

Max. rope diameter / EN 567:	13 mm
------------------------------	-------

Product length:	189.00 mm
-----------------	-----------

Product width:	93.00 mm
----------------	----------

MATERIAL

Material:	Aluminium
-----------	-----------