



KOMORA


CLIMBING ROPE

CE EN1891-A

DIAMETER

Ø 11.7 mm

COLOUR OPTIONS

 TOUCAN

LENGTH OPTIONS

20, 30, 35, 40, 45, 50, 60, 200, 390 &
785 meters

TERMINATION

Available with one spliced eye

This rope has been designed using the very latest innovations in rope manufacturing. Its updated sheath gives superior abrasion resistance and it feeds very smoothly through all popular mechanical friction devices. The core is constructed of X-Braid parallel core technology, it comes with a new slim eye splice and it also features our patented in-eye labelling.

TECHNICAL SPECIFICATIONS



- Materials / construction: 16-strand Polyester sheath with X-Braid Polyamide core
- Static resistance: 30kN
- Resistance with spliced eye: 19kN
- Mass per meter: 94gram
- Sheath percentage: 68%
- Sheath slippage: 0%
- Elongation 50/150Kg: 2.7%
- Knotability: 0.8
- Retraction with water: 2.7%
- Maximum lifespan: 10 years under normal working conditions

Reference: MJF++PZC+++

KEY FEATURES

- Almost no core-sheath slippage
- Superior abrasion resistance
- Heat treated for extra stability
- Retains it's flexibility over time
- Vibrant colour

