

Marlow

DATASHEET®

BOA CORD

Marlow Boa has a hardwearing 16 plait polyester cover with a braided polyester core. This anti-kink construction means Boa is ideal for use as a prussik and other friction hitches, offering easy knot tying and good grip.



PERFORMANCE

NAME	DIAMETER	LENGTHS	WEIGHT		AV. BREAK LOAD		MIN BREAK LOAD	
	mm		g/m	g	kN	kg	kN	kg
Boa Cord	9	-	66	-	25.4	2589	16.2	1650
Boa Loop	9	50	66	71.6	27.4	2793	22	2242
Boa Loop	9	60	66	84.6	27.4	2793	22	2242
Boa Loop	9	70	66	97.7	27.4	2793	22	2242

Key Specifications:

Applications:	Prussik
Material:	Polyester
Lengths:	100 and 200m reels
Colour:	Black/lime
Features:	High tenacity polyester balances economy and performance. Tough 16 plait construction for durability and flexibility

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com



Certificate Number 315
ISO 9001
ISO 14001

www.marlowropes.com

Disclaimer
Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.